

OXYGEN REMOVING PURIFIER FOR HYDROGEN Series 6210

DESCRIPTION

The Series 6210 Purifiers remove oxygen from hydrogen by catalytic action. They are capable of removing up to 1% oxygen from a hydrogen stream down to a level of less than 1ppm. This reaction is normally accomplished at room temperature. At higher oxygen impurity concentrations, somewhat elevated temperatures may be experienced depending on operating conditions.

The purification is carried out by the formation of water from the oxygen impurity and the hydrogen background. If water presents a problem in your system it is suggested that a Model 8010 or 8000 purifier be installed in the system after the Series 6210 unit (see pages 64 and 65.)

The catalytic materials do not require regeneration and will function indefinitely providing that they are not contaminated. Sulfur and halogens are the primary contaminants of concern.



HOW TO ORDER

Model	Max. Flow SCFH	Max. Oper. Press. psig	Connections female	Dimensions inches
6210-10	10	2000	1/4" compression	1.05" dia. x 9.5" long
6210-25	25	2200	1/4" compression	1.32" dia. x 14.5" long
6210-50	50	1200	1/4" compression	1.66" dia. x 15" long
6210-100	100	1400	1/4" compression	2.38" dia. x 15.5" long
6210-200	200	1300	1/4" compression	2.88" dia. x 19.5" long
6210-500	500	900	1/2" compression	4.0" dia. x 23" long